

TECHNICAL SPECIFICATIONS

EXOTIC

INSTALLATION



GLUELESS INSTALLATION (4 SIDE CLIC) manufactured with technology protected by EP 0 843 763 and US 6 006 486



TECHNICAL DATA

USAGE		EN 13329 EN 685	Domestic Intense Commercial Moderate
RESISTENCE TO ABRASION (GROUP)	AC	EN 13329 ANNEX E	AC3
RESISTENCE TO IMPACT (GROUP)	IC	EN 13329 ANNEX F	IC1
CORE			Moisture resistant
SEALED EDGES (paraffin)			YES
ANTI-STATIC		EN 1815	NO
REACTION TO FIRE		EN 13501-1	C _f s ₁
RESISTANCE TO STAINING		EN 438	5 (groups 1 and 2) 4 - group 3
RESISTANCE TO CIGARETTE BURNS		EN 438	4
RESISTANCE TO FURNITURE LEGS		EN 424	No damage visible after testing with type 0 legs
RESISTANCE TO CHAIR CASTORS		EN 425	No visible changes or damage in accordance with regulation 425. Type W castors should be used (EN 12528:1998. SECTION 5.4.4.2)
MOISTURE AT DISPATCH FROM MANUFACTURER		EN 322	Moisture Content between 4 and 10% Batch uniformity: UMax-UMin =<3%
APPEARANCE, SURFACE DEFECTS		EN 438	Minor surface defects are permitted in accordance with EN-438



FINSA

www.finsa.es