

TECHNICAL SPECIFICATIONS

FIRERETARDANT



INSTALLATION



GLUELESS INSTALLATION (4 SIDE CLIC) manufactured with technology protected by EP 0 843 763 and US 6 006 486

USAGE



EN 13329
EN 685

Domestic Intense
Commercial Moderate

RESISTENCE TO ABRASION (GROUP)

AC

EN 13329
ANNEX E

AC4

RESITENCE TO IMPACT (GROUP)

IC

EN 13329
ANNEX F

IC2

CORE



Moisture resistant

SEALED EDGES (paraffin)



YES

ANTI-STATIC



EN 1815

<2KV

REACTION TO FIRE



EN 13501-1

B_fs₁

RESISTANCE TO STAINING



EN 438

5 (groups 1 and 2) 4 - group 3

RESISTANCE TO CIGARETTE BURNS



EN 438

4

RESISTANCE TO FURNITURE LEGS



EN 424

No damage visible after testing with type 0 legs

RESISTANCE TO CHAIR CASTORS



EN 425

No visible changes or damage in accordance with regulation 425. Type W castors should be used (EN 12528:1998. SECTION 5.4.4.2)

MOISTURE AT DISPATCH FROM MANUFACTURER



EN 322

Moisture Content between 4 and 10%
Batch uniformity: UMax-UMin =<3%

APPEARANCE, SURFACE DEFECTS



EN 438

Minor surface defects are permitted in accordance with EN-438



FINSA

www.finsa.es