

# TECHNICAL SPECIFICATIONS

## STYLE



### INSTALLATION



**GLUELESS INSTALLATION ( 4 SIDE CLIC )** manufactured with technology protected by EP 0 843 763 and US 6 006 486

### USAGE



EN 13329  
EN 685

Domestic Intense  
Commercial General

### RESISTENCE TO ABRASION (GROUP)

AC

EN 13329  
ANNEX E

AC4

### RESITENCE TO IMPACT (GROUP)

IC

EN 13329  
ANNEX F

IC2

### CORE



Moisture resistant

### SEALED EDGES (paraffin)



YES

### ANTI-STATIC



EN 1815

NO

### REACTION TO FIRE



EN 13501-1

C<sub>f</sub>s<sub>1</sub>

### RESISTANCE TO STAINING



EN 438

5 (groups 1 and 2) 4 - group 3

### RESISTANCE TO CIGARETTE BURNS



EN 438

4

### RESISTANCE TO FURNITURE LEGS



EN 424

No damage visible after testing with type 0 legs

### RESISTANCE TO CHAIR CASTORS



EN 425

No visible changes or damage in accordance with regulation 425. Type W castors should be used (EN 12528:1998. SECTION 5.4.4.2)

### MOISTURE AT DISPATCH FROM MANUFACTURER



EN 322

Moisture Content between 4 and 10%  
Batch uniformity: UMax-UMin =<3%

### APPEARANCE, SURFACE DEFECTS



EN 438

Moisture Content between 4 and 10%  
Batch uniformity: UMax-UMin =<3%



# FINSA

www.finsa.es