

Maintenance Recommendations

In order for you to enjoy the very best possible performance from your Moduleo® Design Floors, we recommend that you adhere to the following maintenance guidelines.

Moduleo® manufactures a large portfolio of floor coverings with varied specifications and so it is recommended that the floor covering is chosen in accordance with the 'Area of Use' classification shown on supporting literature and/or labels. If you are unsure of the most suitable floor covering for your project's requirements please contact your sales representative or the technical support department.

1. Cleaning and Maintenance for floor coverings with PUR-SUPERGUARD® surface protection

After installation all dirt and dust must be removed from the floor covering. Floor coverings with PUR-SUPERGUARD® surface protection do not need to be pre-treated with a protective gloss starter coat. For everyday cleaning a PU cleaner should be added to water in accordance with the manufacturer's instructions. If some surface damage is apparent after many years of use, Moduleo® recommends a special protective gloss starter coat, or a two-part PU coat treatment is given. This will also offer added protection against chemicals. Never use aggressive agents. To remove dirt use recommended cleaners only. A maintenance programme involving sweeping or vacuuming is also advised. Moduleo® recommends products supplied by the following manufacturers: CC-Dr. Schutz, ECOLAB, RZ CHEMIE, WITTOL Chemie, LOBA, Werner & Mertz, Dr Schnell Chemie, Johannes Kiehl, Diversey Europe. Recommended products have been tested with Moduleo®. Please read the guidelines and instructions of each product before use. If you are unsure of the suitability of certain products, please contact your sales representative or the technical support department of your preferred supplier. These manufacturers have approved the suitability of their respective products on Moduleo® Design Floors.

2. Dirt Barrier Systems

Installing the correct type of entrance matting or dirt barrier system will help to stop nearly 80% of all dirt and moisture carried into buildings. Many benefits can be enjoyed by having an appropriate system in place, including less cleaning and maintenance and a longer first life for the floor covering, both of which will help to maximise the value of your floor covering.

3. Special Notes

Products that may cause bleaching or discolouration should be removed immediately. Chairs should be equipped with castors (Type 'W' in accordance with EN 1259).

The publication of these recommendations and guidelines does not impact upon the ruling standards of the Code of Practice. These recommendations should be considered supplemental to supporting literature. If any points raised within this document need clarification, please contact your sales representative or the technical support department. Moduleo® will not accept responsibility for any claims arising from maintenance not in accordance with these guidelines and recommendations.

A complete list of recommended manufacturers is available from Moduleo® on request. IVC Group reserves the right to make changes or recommendations that do not adversely affect performance or quality.

Avelgem, July 2010